

Model		Specifications																	
		30	50	70	85	95/ 95HD	100	130	150	270	570	900	I/32	I/43	I/53				
Suitable for carrier																			
Weight	min.	t	0.7	0.8	1	2.5	2.5	2.5	4	4	7	12	12	16	25	32			
	max.	t	2	2.5	3.5	7	8	8	12	12	16	25	25	27	37	55			
Operating weight		kg	85	106	140	195	200/245	263	370	370	695	1100	1100	1380	2255	2975			
Height with standard tool & bracket		mm	985	1060	1093	1448	1463/ 1565	1480	1700	1700	2000	2400	2500	2700	3000	3200			
Width		mm	180	180	210	290	290/387	442	452	452	525	512	570	515	616	660			
Tool diameter		mm	40	50	50	62	62	62	74	74	95	115	118	122	150	170			
Flow	min.	l/min	12	18	20	40	55	a 40 b 55	70	90	b 65 c 90	b 80 c 110	100	120	180	240			
	max.	l/min	28	32	50	67	85	65 85	110	150	90 130	120 145	150	170	250	300			
Blow frequency	min.		655	635	640	740	1040	1050	1280	1090	1035	380	415	365	380	400	400	480	415
	max.		1530	1450	2000	1085	1440	1125	1470	1500	1360	625	665	545	510	800	1050	1100	980
Operating pressure max.		bar	135	140	155	120	140	135	145	125	100	75	110	85	125	135	155	155	
Relief valve setting pressure min.		bar	155	160	175	150	180	160	170	180	140	110	145	120	180	180	200	200	
Acceptable back pressure		bar	35	32	32	30	30	27	22	22	3	3	10	6	6	6			
Hose inside diameter																			
	feed	mm	10	12	12	16	16	13	16	19	b 19 c 19	b 19 c 19	19	25	30	32			
	return	mm	12	12	16	16	16	16	19	19	25 30	25 30	25	30	36	36			
Protection against blank firing			yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes			
Automatic stop												yes	yes						
Overflow protection												yes	yes	yes	yes	yes			
Pressure regulation			yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes			
Lubrication			← Grease pump →											option	← Lubrication station →				
METRO-SILENCED noise reduction			← option →												← option →				
- Retrofittable			← yes →												← yes →				

National Distributor

Local Distributor

Nothing contained within this brochure is intended to extend any warranty or representation, expressed or implied, regarding the products described herein. Any such warranties or other terms or conditions of sale of products shall be in accordance with Ingersoll-Rand Standard Terms & Conditions of Sale for such products, which are available upon request. The manufacturer reserves the right to change or delete models and/or specifications without prior notice.

© 1997 by Ingersoll-Rand Company Printed in U.K.

4711A - 4/97

 **MONTABERT**

Ets Montabert S.A.  
203, Route de Grenoble, 69800 Saint-Priest - France  
Tél (33) 472229797 Fax (33) 472229779

Part of worldwide Ingersoll-Rand